



**JPPL**



**FLOOR MARKING TAPES**

# FLOOR MARKING TAPES

## Product Description



It is self colored PE tape coated with an water based pressure sensitive adhesive. These are being widely used now a days for safety, identifying lane marking for storage segmentation, ideal for ISO 9001, QS 9000 companies, good resistance to chemical and other moving object.

## Features

1. Excellent conform ability, particularly to uneven surfaces.
2. Water and UV resistant.
3. Easy remove with no adhesive transfer.
4. Easy way to navigate around a large area.
5. Multiple colors & print option available.

## Standard Sizes

SIZE	PAPER CORE ID
24,36,48,72,96,144 MM	76 MM

## Technical Specification

Type Of Testing	Typical Value	Test Method
Total Thickness	135 Micron	IS : 8402
Peel Adhesion	Min. 750 grams	ASTMD : 1000
Adhesive	Water Based	JPPL Internal
Elongation	240% Min.	ASTMD : 1000
Heat Resistance	100°C	JPPL Internal
Track Rolling Ball	Min. 6	ASTMD : 1000

## Color Codes

Color	Meaning	Application
RED	Danger	Safety cans and signs
Yellow	Caution	Keep fire away, trapping
Orange	Warning	Part of machinery
Green	Safety	Location of first aid equipment.
Blue	Information	Signs and bulleting boards.
Orange Red	Bio Safety	Lables for blood and infectious waste.
Yellow Black	Boundaries	Direction and boards marking.
Magenta Yellow	Radiation Caution	X-ray, alpha, beta, gamma